



Personnel Insulated Door

Aspire Group 360 Ltd

manufactures a wide range of products for Hygienic Temperature Controlled Environments and General Build. We also stock and distribute a complementary range of ancillaries.

Key Features:

- 40mm PIR (Polyisocyanurate)
- 2 no. stainless steel lift off hinges (subject to width & height of door)
- Good thermal properties
- Hermetically sealed
- Suitable for harsh environment
- Light weight construction
- Quick installation





Leaf Construction:

- 40mm PIR Core, faced both sides with white food safe polyester or PVC laminate coated sheet steel, capped with anodised aluminium channel extrusion.

Frame Construction:

- Anodised aluminium two part frame to suit 75mm up to 150mm panel. Other wall thicknesses require special flashings.

Ironmongery:

Locks:

- Euro Profile Mortice Latch, Dead lock, Sash lock, Night Latch, Digital lock

Handles:

- SS Lever Handle fixed on Roses, SS 300 x 19mm "D" Pull Handle bolt thru, SS 350 x 75mm Push Plate, SS Cylinder Pull

Cylinder:

- SS Euro Profile double cylinder, SS Euro Profile single cylinder
- SS Euro Profile Cylinder / Thumb Turn

Panic Furniture:

- Panic latch (1 point), Panic bolt (2 point) c/w External Access Device Door closers

Vision Panels: Various sizes available in:

- Stainless steel finish
- Powder coated finish
- Silicone grey finish
- Anodised aluminium finish

Alternative finishes to door leaf:

- HP200 Plastisol colours.
- Stainless steel: matt, polished
- Glasbord or similar GRP & UPVC.

Door Sizes available: Single, Double, Leaf and Half and Bespoke



Double Swing Personnel Door

Key Features:

- 40mm PIR (Polyisocyanurate)
- Stainless Steel Double-Action spring hinge
- Good thermal properties
- Hermetically sealed
- Suitable for harsh environment
- Light weight construction
- Quick Installation

