



Sliding Chill / Freezer Door

Aspire Group 360 Ltd manufactures a wide range of products for Hygienic Temperature Controlled Environments and General Build. We also stock and distribute a complementary range of ancillaries.

Key Features:

- Temperature range from -40° to + 25°
- Bespoke sizes incorporating cut outs and inner doors features as required
- Suitable for harsh environments
- Quick installation





Sliding Chill / Freezer Door



Leaf Construction:

- Insulated PIR core 40mm, 75mm, 100mm, 150mm finished both sides with white food safe polyester or PVC laminate coated sheet steel capped with Aluminium channel extrusion.

Frame Construction:

- Anodised Aluminium extrusion featuring hidden fixings and appropriate door linings to reveals. Frame can be supplied with or without counterbore holes in frame with black plastic caps

Track:

- Full range of Fermod track systems incorporating standard internal and external handles, gasket and floor guides.

Heaters:

- Low voltage frame and threshold heaters
- Heaters also incorporated in door leaf if required maintain temperature and prevent ice build up

OPTIONS:

- Auto operation : Fermod auto kits to suit relevant track systems
- Door protection finish
- Vision panel
- HP200 plastisol colours
- Stainless steel : Matt, polished or Sullivan circle
- Glasbord or similar GRP
- Meat rail provision if required

